


HOLGER HEUER

Always the right connection


Pipe / Elbow outside diameter 419,0

All details without our obligation



Pipes acc. to DIN 2448 / 2458

Elbows acc. to DIN 2605 (type 2, 3 and 5)



All details relate to 90° elbow

tube od da (mm)	ANSI B 36.10 (mm)	wallthn. s (mm)	pipe weight (kg/m)	type 2		type 3		type 5	
				radius r abt. mm	kg/pce.	radius r abt. mm	kg/pce.	radius r abt. mm	kg/pce.
419,0		6,3	64,3	400 +/- 25,0	40,3	609,5 +/- 10,0	61,4	1000 +/- 25,0	101
419,0		8	80,7	400 +/- 25,0	51	609,5 +/- 10,0	77,6	1000 +/- 25,0	127
419,0		10	101	400 +/- 25,0	63,4	609,5 +/- 10,0	96,6	1000 +/- 25,0	158
419,0		11	111	400 +/- 25,0	69,5	609,5 +/- 10,0	106	1000 +/- 25,0	174
419,0		12,5	125	400 +/- 25,0	78,7	609,5 +/- 10,0	120	1000 +/- 25,0	197
419,0		14,2	142	400 +/- 25,0	89,1	609,5 +/- 10,0	136	1000 +/- 25,0	223
419,0		16	159	400 +/- 25,0	99,9	609,5 +/- 10,0	152	1000 +/- 25,0	250
419,0		17,5	173	400 +/- 25,0	109	609,5 +/- 10,0	166	1000 +/- 25,0	272
419,0		20	197	400 +/- 25,0	124	609,5 +/- 10,0	188	1000 +/- 25,0	309
419,0		22,2	217	400 +/- 25,0	137	609,5 +/- 10,0	208	1000 +/- 25,0	341
419,0		25	245	400 +/- 25,0	153	609,5 +/- 10,0	233	1000 +/- 25,0	382

Holger Heuer Exportservice eKfm

Ring 18 · D-27777 Ganderkesee / Germany

P.O. Box 1514 · D-27766 Ganderkesee / Germany

Phone: **49 42 22 / 95 02 32 · Fax: **49 42 22 / 95 02 33

Website: www.connectors.de · E-mail: mail@connectors.de